

---

# Subverting Operating System Properties through Evolutionary DKOM Attacks

---

Mariano Graziano, Lorenzo Flore, Andrea Lanzi, Davide Balzarotti

Cisco Systems, Inc.  
Universita' degli Studi di Milano  
Eurecom

DIMVA 2016 - San Sebastian, Spain

TALOS


# TRADITIONAL DKOM ATTACKS

---



# TRADITIONAL DKOM ATTACKS

---




# TRADITIONAL DKOM DEFENSES

---

- ▶ Kernel data integrity solutions:
  - ▶ invariants
    - ▶ external systems
    - ▶ memory analysis
  - ▶ data partitioning

# EVOLUTIONARY DKOM ATTACKS


---



data structure of interest

# EVOLUTIONARY DKOM ATTACKS

---




Violation of a temporal property



# EVOLUTIONARY DKOM ATTACKS

---



Violation of a temporal property

the attack cannot be detected looking at a single snapshot

# STATE VS PROPERTY

---


- ▶ Traditional DKOM affects the **state** and are **discrete**
- ▶ Evolutionary DKOM (E-DKOM) affects the evolution in time of a given **property** and are **continuous**

# THREAT MODEL


---

- ▶ Attacker has access to ring0
- ▶ Malicious code not detectable by current solutions
- ▶ Attacker cannot modify kernel code and attack the VMM


# EXAMPLE: LINUX CFS SCHEDULER



# SUBVERTING THE SCHEDULER



# SUBVERTING THE SCHEDULER






# SUBVERTING THE SCHEDULER

```
struct task_struct {
    volatile long state;
    void *stack;
    unsigned int flags;
    int prio, static_prio, normal_prio;
    const struct sched_class *sched_class;
    struct sched_entity se;
    ...
}

struct cfs_rq {
    ...
    struct rb_root tasks_timeline;
    ...
};
```

```
struct sched_entity {
    struct load_weight load;
    struct rb_node run_node;
    struct list_head group_node;
    ...
}
```



We affected the **evolution** of the data structure over time. We altered the scheduler **property** (fair execution).

# ATTACK EVALUATION

---


- ▶ Temporarily block an IDS or Antivirus
- ▶ Temporarily block Inotify

# DEFENSES?


---

- ▶ Reference monitor that mimics the OS property:
  - ▶ OS specific
  - ▶ Difficult to generalize


# DEFENSE FRAMEWORK




# DEFENSE FRAMEWORK




# DEFENSE FRAMEWORK



# OVERHEAD



Normal operations



Stress test

TALOS

# CONCLUSIONS

---

- ▶ New DKOM attack based on data structures evolution
- ▶ Experiment on the Linux CFS scheduler
- ▶ Defense solution based on hypervisor
- ▶ General mitigation/solution very hard

# QUESTIONS?

Mariano Graziano  
magrazia@cisco.com  
@emd3l

